

imageRUNNER
C3326i

Canon
Delighting You Always

ELEVATING WORKSPACE PERFORMANCE

Functional and Efficient



Business Can Be Simple

ENHANCING WORKSPACES

With a multitude of functions that drive productivity, the new imageRUNNER C3326i offers time-saving and efficient solutions in the modern workplace.



EASE OF ACCESSIBILITY

Tap into a rich variety of functions through the built-in 7-inch operation panel, which is fully customisable to accommodate for organisation of commonly used processes. The Timeline feature displays past job histories which can be conveniently re-executed at a touch, making processes easy for users who repeatedly utilise the same functions and settings.



EFFICIENT DOCUMENT SCANNING

Ensure optimal readability and orientation of scanned documents with the Scan Preview function. Simply review scanned items on the display to rectify any scanning errors before sending, saving time and providing added convenience.

EFFORTLESS DOCUMENT HANDLING

The new multi-functional device offers various finishing options to further ease workflow. Select from ECO-staple, Staple-On-Demand and hole-punching functions that reduces the need for manual collating and stapling.

8

SHEETS

ECO-STAPLE

Up to 8 sheets
(A4/80 gsm)

50

SHEETS

STAPLE-ON-DEMAND

Up to 50 sheets
(A4/80gsm)



SECURE DATA PROTECTION

Worry less about data being compromised using advanced and up-to-date security features in the imageRUNNER C3326i. Keep documents safe with authentication and encryption.

Securing Document Access

Manage important or confidential documents securely to prevent leakage of information. The Force Hold Print feature holds the documents at the device and releases it only upon authentication, preventing accidental or unwanted access.



Encrypted PDF to prevent leakage of information

Preventing Risks

Scanned documents in formats like PDF or XPS can be encrypted to secure their digital data with an additional layer of protection alongside limiting access only to the right document handler.



User authentication features to manage access

uniFLOW Online/ Online Express

The imageRUNNER C3326i offers login authentication with uniFLOW Online Express, providing additional document security functions while granting access only to permissible users.



Specifications

MAIN UNIT	
Machine Type	A3 Colour Laser Multifunctional
Core Functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	7 inch TFT LCD WVGA Colour Touch panel
Memory	Standard: 2.0GB RAM
Storage	Standard: 64GB eMMC (available space 30GB) Optional: 256GB SSD
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
	Others Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80gsm)	Standard: 1,200 sheets (100 sheets Multi-purpose tray, 2 x 550 sheets paper cassette) Maximum: 2,300 sheets (with Cassette Feeding Unit-AW1)
Paper Output Capacity (A4, 80gsm)	Standard: 250 sheets Maximum: 645 sheets (with Inner Finisher-L1 and Copy Tray-T2)
Supported Media Types	Multi-purpose tray: Thin, Plain, Heavy, Recycled, Coated ¹ , Colour, Tracing, Bond, Transparency, Labels, Pre-punched, Letterhead, Envelope, Postcard ¹ SRA3 is unsupported for Coated (257 to 300 gsm)
	Upper Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope ¹ , Postcard ¹ Envelope Feeder Attachment Kit B (standard) is required except ISO-C5.
	Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope ¹ , Postcard ¹ Envelope Feeder Attachment Kit A (standard) is required.
Supported Media Sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm
	Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelopes: ISO-C5
	Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes ¹ : COM10 No.10, Monarch, DL ¹ Envelope Attachment A (standard) is required.
Supported Media Weights	Multi-purpose tray: 52 to 300 gsm ¹ ¹ SRA3 is unsupported for Coated (257 to 300 gsm). Paper weight supported with Media Adjustment Kit-A1: 60 to 300gsm.
	Upper/Lower Cassette: 52 to 256 gsm Duplex: 52 to 220 gsm
Warm-up Time (Quick start mode: ON)	4 Seconds or Less ¹ ¹ Time from device power on to when copy icon appears and is enabled to operate on the touch panel display.
	From Sleep Mode: 10 seconds or less
	From Power On: 10 seconds or less ¹ ¹ Time from device power-on, until copy ready (not print reservation)
Dimensions (W x D x H)	With Platen Cover-Y3: 565 x 659 x 788 mm With DADF-BA1: 565 x 687 x 891 mm
Installation Space (W x D)	Basic: 978 x 1,088 mm (with Platen Cover-Y3 + right door & multi-purpose tray opened + paper cassette opened) Fully Configured: 1,286 x 1,116 mm (with DADF-BA1 + Inner Finisher-L1 + Copy Tray-T2 extended + paper cassette opened)
Weight (Including toner)	With Platen Cover-Y3: Approx. 71 kg With DADF-BA1: Approx. 78 kg
PRINT SPECIFICATIONS	
Print Speed (BW)	1-sided: Up to 26 ppm (A4), Up to 15 ppm (A3), Up to 20 ppm (A4R)
Print Resolution (dpi)	600 x 600, 1,200 x 1,200 (half-speed)
Page Description Languages	Standard: UFR II, PCL6 Option: Adobe PostScript 3
Direct Print (RUI)	PDF, EPS, TIFF/JPEG and XPS
Printing from Mobile and Cloud Applications	AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ¹ (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts ² ¹ Optional PCL International Font Set-A1 is required. ² Optional Barcode Printing Kit-D1 is required.
Operating System	UFR II: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS(10.13 or later)
	PCL: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022
	PS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS(10.13 or later) PPD: Windows® 10/11, macOS(10.13 or later)

COPY SPECIFICATIONS	
Copy Speed (BW/CL)	1-sided: Up to 26 ppm (A4), Up to 15 ppm (A3), Up to 20 ppm (A4R)
First-Copy-Out Time (A4, BW/CL)	Approx. 7.0/8.7 seconds or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%(1:1), 115%, 122%, 141%, 200%, 400%
SCAN SPECIFICATIONS	
Type	Option: Platen Cover-Y3 or DADF-BA1(2-sided to 2-sided)
Document Feeder Paper Capacity (80 gsm)	Up to 100 sheets
Acceptable Originals and Weights	Platen: Sheet, Book and 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)
Supported Media Sizes	Platen: Max. scanning size: 297.0 x 431.8 mm
	Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm
Scan Speed (ipm: BW/CL; A4)	DADF-BA1: 1-sided Scanning: 70/70 (300 x 300 dpi, send), 51/42 (600 x 600 dpi, copy) 2-sided Scanning: 35/35 (300 x 300 dpi, send), 25.5/25.5 (600 x 600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/iFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
Pull Scan Specifications	Color Network ScanGear2: For both TWAIN and WIA
Supported OS	Supported OS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV Optional: Super G3 FAX
Address Book	LDAP (2,000)/Local (1,600)/One-touch (200)
Send Resolution (dpi)	Push: (CL) up to 300 x 300/(BW) up to 600 x 600 Pull: (CL) up to 300 x 300/(BW) up to 600 x 600
Communication Protocol	FTP: (TCP/IP), SMB3.1.1(TCP/IP), WebDAV Email/iFax: SMTP(send), POP3(receive)
File Format	Standard: TIFF (MMR), JPEG ¹ , PDF (Compact, OCR (Text Searchable)), Optimise PDF for Web, Format to PDF/A-1b, Encrypt), XPS (Compact, OCR (Text Searchable)), PDF/XPS (Device Signature), Office Open XML (PowerPoint, Word) Option: PDF (Trace & Smooth), PDF/XPS (User Signature) ¹ Single-Page only.
FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3:14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Recording Size	Sending: A3, A4, A4R, A5 ¹ , A5R ¹ , B4, B5 ² , B5R ¹ Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R ¹ Sent as A4 ² Sent as B4 short
FAX Memory	Up to 30,000 pages (2,000 jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power Source	220-240V, 50/60Hz, 5A
Power Consumption	Maximum: Approx. 1,500W Sleep Mode: Approx. 0.8W ¹ ¹ 0.8W is not available in all circumstances due to certain settings.
CONSUMABLES	
Toner Yield (Estimated @ 5% Coverage)	NPG-88 Toner BK: 38,000 pages NPG-88 Toner C/M/Y: 25,500 pages NPG-88L Toner C/M/Y: 4,000 pages
OTHER ACCESSORIES	
DADF-BA1, Platen Cover-Y3, Cassette Feeding Unit-AW1, Inner 2Way Tray-M1, Copy Tray-T2, Inner Finisher-L1, Inner 2/3 Hole Puncher-D1, Inner 2/4 Hole Puncher-D1, IC Card Reader Attachment-B4, Option Attachment Kit For Reader-A2, Utility Tray-B1, Media Adjustment Kit-A1, PS Printer Kit-CS1E, PCL International Font Set-A1E, PCL Asian Font Set-A1E, Barcode Printing Kit-D1E, Universal Send Trace & Smooth PDF Kit-A1E, Universal Send Digital User Signature Kit-C1E, Super G3 Fax Board-BN1, Remote Fax Kit-A1, Optional Data Storage Kit-A1, Copy Control Interface Kit-D1, ADF Access Handle-A1, Staple-P1	



SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.
1 Fusionpolis Place # 14-10 Galaxis, Singapore 138522
Tel: 65-6799-8888 | Fax: 65-6799-8882 | <https://asia.canon>