

## JustPerfect.

**Boundless Versatility Made Affordable** 



The brand new **imagePROGRAF** 36" **TM-5340** and 24" **TM-5240** large format printers provide scalability alongside affordability in small home office printing for photos, CAD drawings and other multi-application prints. Discover greater versatility as well as accessibility in delivering quality prints ideal for your business requirements.

# Versatile and Affordable High-Quality Printing

Designed to provide affordable and quality results for a wide range of printing applications, the new **imagePROGRAF** 36" **TM-5340** and 24" **TM-5240** large format printers help to meet the requirements of engineering firms with versatility in cost and printing.

## **Swift Speeds for Greater Productivity**

The new L-COA PRO II high-speed imaging processing chip provides enhanced data processing power for the TM-5240 and TM-5340, enabling faster turnaround times from sleep mode as well as continuous printing for greater productivity overall.



## **Enhancing Details Through Vivid Red**

The **new magenta ink** helps to deliver a vivid red that highlights important details on photos, posters as well as CAD drawings with greater clarity.



## **Effortless User Operation**



## **Streamlining Workflows with Intuitiveness**

Experience greater printing convenience with software applications designed to streamline the management of workflows.



#### **Free Layout Plus**

Free Layout Plus allows files to be dragged and dropped into the application for the easy resizing of documents to fit specific paper layouts before printing.



#### **Accounting Manager**

**Monitor print usage** with greater ease through **Accounting Manager**.

#### **PosterArtist**

PosterArtist

The **PosterArtist** application offers effortless creation of **vibrant and visually appealing posters**.

Check it out at https://posterartist.canon

#### **Direct Print Plus**

Print PDF or JPEG files in batches effortlessly with custom templates by using Direct Print Plus.



## **Quality with Affordability**

Enjoy affordable and high-quality printing with **55ml small capacity ink tanks** best suited for the needs of small businesses or startups.



## **Enhanced Scanning Capabilities**

The TM-5240 and TM-5340 can be utilised alongside a scanner with enhanced capabilities that improve scanning productivity and operability by offering a maximum paper thickness of 0.8mm as well as featuring new transparent guides.





TM-5240 Lm24 Scanner

TM-5340 Lm36 Scanner

#### **SPECFICATIONS**

PRINTER		TM-5240	TM-5340	
Printer Type		5-Colour, 24" 5-Colour, 36"		
Number of Nozzles Max. Print Resolution		15,360 nozzles (MBK 5,120 nozzles, Other Colours 2,560 nozzles each) 2,400 x 1,200 dpi		
Nozzle Pitch		2,400 x 1,200 api 1,200 dpi × 2		
Line Accuracy*1		± 0.1 % or less		
Sales Ink		55 ml (MBK, BK, C, M, Y)		
Ink Tank Size	Bundle	55 ml (MBK, BK, C, M, Y)		
	Starter Ink			
Ink Type		Pigment Ink SG Pactor (Swift Graphia Pactor)		
		SG Raster (Swift Graphic Raster) HP-GL/2, HP RTL		
Print Languages  Print Solutions & Applications		JPEG		
		CALS G4*2		
		Printer Driver (Win/Mac versions), Direct Print Plus, Free Layout plus, PosterArtist Windows/Web & Lite, Wi-Fi Connection Assistant, PIXMA Cloud Link, Apple AirPrint (Mobile), Canon PRINT Inkjet/SELPHY (Mobile),		
		Canon Print System (Mobile), uniFlow server		
Management Solutions		Media Configuration Tool (Includes Color Customisation Tool), Accounting Manager, Device Management Console, Quick Utility Toolbox		
	USB B Port	Hi-Speed USB, Full Speed (12 Mbit/sec), Hi-Speed (480 Mbit/sec),		
	USB A Port	Bulk Transfer, Series B (4 pins)  NA		
		IEEE 802.3 10base-T		
		IEEE 802.3u 100base-TX		
Interface	Network	IEEE 802.3ab 1000base-T		
(Built-In)		IEEE 802.3x Full Duplex SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP		
		IEEE802.11 b/g/n		
		WPA-PSK (TKIP/AES)		
		WPA2-PSK (TKIP/AES)		
	Wireless LAN	WPA3-SAE (AES)		
		WPA-EAP (AES)*3 WPA2-EAP (AES)*3		
		WPA3-EA	P (AES)*3	
Memory		2 GB		
Display		LCD (4.3 inch / 10.9 cm TFT color)		
OS Compatability	Please visit https://asia. canon to confirm OS compatibility and to download the latest drivers.	Windows, Macintosh		
SCANNER				
Scanner Model		Lm24	Lm36	
Scan Width		24"	36"	
Optical Resolution (DPI)		Up to 600 dpi		
Scan Format		TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG		
Scan Destinatio	ns	Scan to PC, USB		
Scanner Softwa	re	ScanAPP		
		Colour		
		Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec		
Max. Copy Spee		Best (600/600 dpi): 0.5 ips / 12.7 mm per sec		
(inch/sec) or (m	m/sec)	Monochrome		
		Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec		
		Best (600/600 dpi): 1.5 ips / 76.2 mm per sec		
Max. Scan Speed: (inch/sec) or (mm/sec)		Colour		
		Draft (200 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec		
		Best (600 dpi): 0.33 ips / 8.38 mm per sec		
		Monochrome		
		Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec		
Maximum Original		Up to 0.8 mm		
Thickness & Lei	ngth	·		
PRINT SPEED*4	CAD Drawing	A1 Size	A0 Size	
Plain Paper	(Fast Q5 mode)	23 sec	41 sec	
Heavyweight	Poster			
Coated Paper	(Standard mode)	1 min 45 sec	3 min 10 sec	
		l .	L	

#### Specifications are subject to change without notice.

- User adjustments required. Printing environment and media must match those used for the adjustments. Paper required: Plain paper and coated paper only.
- \*2 USB Thumb drive printing is not supported.
- \*3 IEEE802.1X (EAP-TLS/EAP-TTLS/PEAP) Supported.

MEDIA HANDLII		TM-5240	TM-5340	
Media Width	Roll Paper	203.2 ~ 610 mm	203.2 ~ 917 mm	
media Widii	Cut Sheet	200.2 010 11111	200.2 017 11111	
Media	Roll Paper /	0.07 ~ 0.8 mm		
Thickness	Cut Sheet	0.07 ~ 0.8 mm		
Printable	Roll Paper	203.2 mm ~ 18 m*5		
Media Length Cut Sheet		279.4 ~ 1,600 mm		
Media Core Size		2 inch (Default) / 3 inch core (Optional)		
Outside Diameter Roll Paper		150 mm or less		
Roll Paper		1 Roll, Top Load, Front Output		
Media Feed Cut Sheet		Front Load, Front Output		
Dolivory Directio		Face-up, Front side		
Delivery Direction	r	1 doe up, 1 totte side		
	Recommended Area	20 mm, 3 mm, 3 mm		
	(Roll Paper)			
	Recommended			
	Area	20 mm, 20 mm, 3 mm		
Margins	(Cut Sheet)	,		
(Top, Bottom,	Printable Area	0		
Side)	(Roll Paper)	3 mm, 3 mm, 3 mm		
	Printable Area			
	(Roll Paperless	0 mm		
	Print)			
	Printable Area	3 mm, 20 mm, 3 mm		
	(Cut Sheet)			
DIMENSIONS (V	VxDxH) & WEIGH	T*6		
	TM-5240			
	Printer	1,147 x 874 x 542 mm	NA	
	(Main unit	Weight: 50 kg		
	with pallet)			
	TM-5240			
	Stand + Basket (SD-24)	4050 000 000		
	` '	1,058 x 826 x 270 mm	NA	
Dealerand	TM-5340 Stand +	Weight: 20 kg		
Packaged Dimensions	Basket (SD-33)			
Dimensions	TM-5240			
Weight	Printer			
	(Main unit			
	with stand and			
	pallet) (SD-24)	1,152 x 912 x 679 mm	1,462 x 913 x 801 mm	
	TM-5340	Weight: 71 kg	Weight: 100 kg	
	Printer			
	(Main unit			
	with stand and			
	pallet) (SD-33)			
	Printer	978 x 748 x 439 mm	1,285 x 748 x 439 mm	
	T14 5040	Weight: 40 kg	Weight: 47.5 kg	
	TM-5240			
Printer & Weight	Printer with Stand + Basket	978 x 868 x 1,060 mm	1,285 x 868 x 1,060 mm	
	(SD-24)	(Basket Opened)	(Basket Opened)	
	TM-5340	978 x 756 x 1,060 mm	1,285 x 756 x 1,060 mm	
	Printer with	(Basket Closed)	(Basket Closed)	
	Stand + Basket	Weight: 50.9 kg	Weight: 59.2 kg	
	(SD-33)			
Scanner & Weig	ht	935 x 253 x 131 mm	1,238 x 253 x 131 mm	
_		Weight: 5.28 kg	Weight: 6.56 kg	
	ERATING REQUI			
Power Supply (P		AC 100-240 V		
Power	Print Operation	Operation: < 59 W	Operation: < 65 W	
Consumption	Sleep Mode		6 W	
(Printer)	Power OFF	< 0.1 W		
Recommended	Temperature	Temperature: 15-30 °C		
Environment	Humidity	Humidity: 10-80 % RH (no dew condensation)		
Acoustic	Power*7	Approx. 6.0 Bels		
Acoustic	Pressure*7	Approx. 39 dB(A), Standby 35 dB(A) or less		
OPTIONAL ACC	ESSORIES			
Roll Unit		-	-	
2/3" Roll Holder		RH2-28	RH2-35	
Printer Stand + Basket		SD-24	-	
Card Reader Interface for				
uniFLOW		RA-02		
CONSUMABLES				
Magenta: PEI-8031 (55 ml)				
Ink Tank		Matte Black / Black / Cyan / Yellow: PFI-8030 (55 ml)		
Print Head		PF-06		
Cutter Blade		CT-08		
Maintenance Cartridge		C1-08 MC-31		

- $^{\ast 4}$  Time taken to print one page does not include time required for data.
- $^{\ast_{5}}$  Varies according to the OS and application.
- \*6 Include roll holder set.

Maintenance Cartridge

\*7 Acoustic Power and Pressure are measured using ISO 7779 standard.



### SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

Delighting You Always 1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel : 65-6799-8888 | Fax : 65-6799-8882 | https://asia.canon

#### **DEALER'S STAMP**

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

MC-31